


MOLYDUVAL

Soraja VA 68



Vacuum Pump Oil for Food Processing Facility

A synthetic lubricating oil based on polyalphaolefines for vacuum pumps in the food and pharmaceutical industries. In addition to excellent high and low temperature stability, it offers wear protection, good seal compatibility and excellent lubricity.

Characteristics

- compatible with mineral oil
- low pour point
- long usability due to good oxidative resistance
- Relatively well compatible with elastomers and plastics (ask for exact compatibility)
- good viscosity temperature correlation
- Food grade, conforms to the NSF H1 regulations for use in Food Industry

Applications

- for vacuum pumps, mechanical and diffusions pumps
- for milk machines

Technical Datas

Color		transparent
Base Fluid		PAO
Viscosity Class	ISO-VG	68
Viscosity 40°C	mm ² /s	68
Viscosity 100°C	mm ² /s	9
Viscosity Index		142
Density 40°C	kg/m ³	840
Flash Point COC	°C	232
Pour point	°C	-40
No MOAH		meets (*)
NSF H1		meets (*)
Pack Size can 5 l		+
Pack Size can 20 l		+
Pack Size drum 200 l		+

() We do not have a direct approval. The product is manufactured solely in accordance with the approval. Therefore, compliance with the parameters specified in the approval cannot be guaranteed.*