


MOLYDUVAL

Soraja HA 15



Hydraulic Oil for Food Industry

A synthetic industrial hydraulic fluid with good high temperature stability and wear protection. Based on modern Food - grade and USDA H1 cleared Polyalphaolefines (PAO), it has a good seal compatibility, good corrosion protection and a top high temperature stability. Available even in many other ISO and SAE viscosity classes. It may replace mineral oils in food and pharma industry and therefore represents a step to more safety and cleanness.

Properties

- * compatible with mineral oil
- * high pressure ability
- * longer service life due to high thermal stability
- * relative good seal compatibility, please ask for precise information in regard to your material
- * Food grade, i.e. the product fulfills the requirements for an H1 lubricant for use in the food industry
- * excellent viscosity temperature behaviour

Applications

- * for hydraulic equipment in food and pharma industry
- * for bearings of oven conveyors, as in annealing and drying furnaces, bakery ovens, rotary kilns
- * as sliding agent to plastics, in printing or textile industry
- * for bearings in refrigeration equipment
- * for rolling and sleeve bearings in food and pharma industry

Technical Datas

Color		transparent
Name		CLPHC15
Base Fluid		PAO
Viscosity Class	ISO-VG	15
Density 20°C	kg/m ³	815
Temperature Range	°C	-50 -> +120
Pour point	°C	-66
Viscosity 40°C	mm ² /s	16
Viscosity 100°C	mm ² /s	3
Flash Point	°C	220
Viscosity Index		120

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website <https://www.solano-industries.com/en/>

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.