



MOLYDUVAL

Aero BA 20



Synthetic Low Temperature Grease

A soft synthetic low temperature grease manufactured from a synthesized hydrocarbon fluid (PAO) and a non soap bentone thickener for lubrication of small gears, joints and sleeve bearings at low and high temperatures. Frost and water resistant. It is easy to apply and pump at low temperatures.

Characteristics

- good anticorrosive properties
- water refusing
- strong tackiness
- extreme frost resistant
- good walking resistance
- relative good compatible with many usually used sealants
- low starting torque
- compatible with many seals and plastics

Applications

- for instruments in precision engineering
- for small gear units in medicinal or pharmaceutical equipment
- for spindles
- for tachometer axles
- for gears and bearings in flight safety equipment, control devices in aeronautics
- for lubrication of contacts in precision engineering
- for valves and seals in vacuum and aeronautic

Technical Datas

Color		brown
Base Fluid		PAO
Name		GP00N-60
Consistency Class NLGI		ca. 00
Viscosity Base Fluid, 40°C	mm ² /s	32
Density 15°C	kg/m ³	860
Temperature Range	°C	-60 -> +140

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.



For further information, please see our website www.solano-industries.com/en/

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 09.07.2024