



MOLYDUVAL

Amadeus M 32



Vacuum Pump Oil

A vacuum pump fluid for use in a wide variety of vacuum compressors.

Characteristics

- good anticorrosive properties
- oxidation resistant
- high viscosity index
- relative low residue forming
- high flash point
- low foam forming
- good demulsifying properties

Applications

- for vacuum pumps, mechanical and diffusions pumps

Technical Datas

Color		yellow
Viscosity Class	ISO-VG	22/32
Viscosity 40°C	mm ² /s	27
Viscosity 100°C	mm ² /s	6
Density 40°C	kg/m ³	880
Pour point	°C	-12
Flash Point COC	°C	220
Color		0,5
DIN 51501 L-AN		meets
DIN 51515 L-TD		meets
DIN 51517 T2 CL		meets
DIN 51524 T1 HL		meets
Pack Size can 5 l		+
Pack Size drum 200 l		+



For further information, please see our website www.solano-industries.com/en/

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 14.03.2025