


# MOLYDUVAL

## Ferroxin DEC Spray



### Biodegradable Chain and Wire Rope Grease

A highly adhesive, biodegradable lubricating and anti-corrosion grease for chains and wire ropes in rough operation. It forms a well adhering, greasy, graphitized coating with very good water resistance. Contains solid lubricants that reduce friction and reduce the risk of fretting corrosion.

#### Characteristics

- contains the solid lubricant graphite offering additional friction reducing
- very good water resistance
- fast biodegradable
- protects against corrosion caused by salt and humidity
- good tackiness
- protects the braid
- protects the wire ropes
- protects the rope
- adhesive

#### Applications

- for bearings at funnels and weirs
- for conservation and lubrication of wire ropes
- for chains in sensitive areas
- for chains and wire ropes on ships

#### Technical Datas

Color		black
Density 15°C	kg/m <sup>3</sup>	1000
Temperature Range	°C	-30 -> +150
Water Resistance Static	Grade	0
Wear Protection VKA welding load	N	> 4000
solids	--	Graphite
Pack Size spray can 400 ml		+

*The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.*

For further information, please see our website [www.molyduval.com](http://www.molyduval.com) or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 04.11.2024