




MOLYDUVAL

Emulator GE Spray



Separating Agent for Thermoplastics

A silicone free release and lubrication agent for rubber, plastics and many types of resins. When sprayed or brushed on surfaces, it leaves a thin film with excellent releasing and lubrication properties without having any solvent or swelling effect on the products. Used as a release agent in plastics and rubber industry as well as for maintenance of plastic parts.

Characteristics

- good anticorrosive properties
- biodegradable
- free of silicones
- good separating properties
- low viscosity, easy handling
- free of solvents
- water free
- high percentage of effective substances

Applications

- as release agent for plastic and rubber molds, foams, and latex
- as sliding agent to plastics, in printing or textile industry
- as release agent for plastic molds
- as parting agents when pressing, syringe, vacuum-forms, e.g. during the elastomer production and in the plastic processing industry
- as sliding and lubricant for mobile parts such as measurers and cuts

Technical Datas

Color		transparent
Viscosity 40°C	mm ² /s	40
Density 40°C	kg/m ³	910
Flash Point COC	°C	290
Pour point	°C	-18
Pack Size spray can 400 ml		+

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 28.02.2025