


# MOLYDUVAL

## Moralub TZL Spray



### Synthetic Metal Working Spray

A synthetic low viscous metalworking oil in the spray can, based on synthetic hydrocarbons and strong polar active substances. For normal non-cutting metal forming. Preventing wear, increases the tool life, lowers tooling expenses, applicable for rust-and acid-proof steel sheets and steel sheets in deep-drawing quality.

#### Properties

- \* economic in use
- \* good heat deduction
- \* friendly smell
- \* low wear, long tool life

#### Applications

- \* for tool and workpiece lubrication in cold metal forming like deep throwing or squeezing
- \* for stamping and deridging of die casting workpieces
- \* for cold flow pressing
- \* for metall forming
- \* for cold forming of metals

#### Technical Datas

Color		transparent
Base Fluid		PAO
Viscosity Class	ISO-VG	5-10
Flash Point	°C	160
Density 15°C	kg/m <sup>3</sup>	800
Temperature Range	°C	-70 -> +150
Pour Point	°C	-73
Unit	ml	400

*The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.*



For further information, please see our website <https://www.solano-industries.com>

The technical data in this information sheet represents our present knowledge and is based on our general experience. It is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product to ensure that the product is safe, effective and fully satisfactory for the intended end use. It does also not form part of any sales contract as guaranteed properties of the delivered material.