

TECHNICAL DATA SHEET

VENOL VENLUB RSX CLP 220

APPLICATION:



RSX-CLP and RSX-SP oils are intended for industrial gears. These are gear oils commonly used in gears of machines and devices operating in very difficult conditions, which require an oil with increased oil film resistance to loads, good oxidation resistance, and good anti-corrosion and deemulsifying properties. These oils contain EP-type sulfur-phosphorus additives. They are miscible with other branded oils of this type



VENOL VENLUB RSX SP	Typical values					
ISO VG viscosity class	68	100	150	220	320	460
Kinematic viscosity at 40°C [mm ² /s]	67	99	152	225	315	450
Viscosity index	105	105	115	120	130	135
Pour point [°C]	-21	-20	-20	-18	-18	-15
Flash point [°C]	240	240	240	245	250	250

VENOL VENLUB RSX CLP	Typical values					
ISO VG viscosity class	68	100	150	220	320	460
Kinematic viscosity at 40°C [mm ² /s]	67	99	152	225	315	450
Viscosity index	105	105	115	120	130	135
Pour point [°C]	-21	-20	-20	-18	-18	-15
Flash point [°C]	240	240	240	245	250	250



Due to continuous product development, the information contained herein is subject to change without notice.

For further information, please see our website <https://www.solano-industries.com>