



MOLYDUVAL

Sekorex PLX



An very adhesive chain lubricant for very high loaded, slow running chains. Because of its good water resistance and oxidation stability it is even useful under corrosive conditions. It is a black grease containing the solid molybdenum disulphide for reduced friction and emergency run properties.

Characteristics

- good anticorrosive properties
- exceptional lubricating and separating properties
- prevents seizure and rust
- very high pressure ability
- reduces risk of tribo corrosion
- reduced friction coefficient with increasing pressure
- reduces wear and friction
- reduces risk of Stick-Slip-effect
- reduces friction in running in phase
- very good tackiness
- resistant to water
- offers emergency running property
- dust refusing, rejects dust and dirt

Applications

- for open gears
- for chains in high temperature sectors
- for chain lubrication in dusty surroundings
- for chains in textile industry
- for chains on bouw machines, lifters, mills
- for wire ropes in power plants
- for chains at energy plant, f.e. chains of burner cleaning equipment

Technical Datas

| | | |
|--|----|--------------|
| Color | | grey |
| Base Fluid | | Syn |
| Temperature Range | °C | -25 -> + 200 |
| Temperature Range dry lubrication, solid lubrication | °C | 450 |
| Pack Size can 5 l | | + |
| Customs tariff number | | 271019 |

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website <https://www.solano-industries.com>