


MOLYDUVAL

Sekorex ET 1500 P



Synthetic High Temperature Chain Oil

A 100% synthetic ester based, high treated heavy viscosity lubrication oil for high temperature chains. Besides of it's excellent high temperature stability it guarantees excellent wear protection and good corrosion protection. Qualified for chains and even suitable for bearings, slides and sliding surfaces at high temperatures. In case of very high temperatures it forms only less residues, and evaporates low.

Characteristics

- very high pressure ability
- compatible with mineral oil
- free from mineral oil
- low smoke formation
- low evaporation
- good low temperature characteristics
- low residues
- low noise
- high flash point
- good ageing resistance
- harmless
- low residue forming
- strong tackiness caused by very long molecules

Applications

- for chains in high temperature sectors
- for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- for chains in textile industry
- for chains in drying ovens, painting ovens, baking ovens, e.g. in the production of plasterboard and chipboard as well as glass or rock wool
- for printing machines, central lubrication systems

Technical Datas

Color		yellow
Basis		ester
Viscosity 40°C	mm ² /s	1500
Viscosity 100°C	mm ² /s	83
Density 40°C	kg/m ³	920
Temperature Range	°C	0°C -> +260°C
Pack Size can 5 l		+
Pack Size drum 60 l		+
Pack Size drum 200 l		+

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website <https://www.solano-industries.com/en/>