

MOLYDUVAL

Attila AM 2



Fittings Grease

A special grease for lubrication and sealing of taps and valves. Based on mineral oil with an aluminum soap thickener.

Properties

- * oxidation resistant
- * good lubrication performance
- * very good tackiness
- * relative good compatible with many usually used sealants
- * no resin forming
- * withstands weak acids and alkaline solutions

Applications

- * for fittings, for example cocks and plugs
- * for sealing conical valves
- * for control systems in heaters

Technical Datas

Color		green
Consistency Class NLGI		2
Base Fluid		Min
Density 15°C	kg/m ³	920
Water Resistance Static	Grade	0-90
Temperature Range	°C	-10 -> +100
oxidation resistance	kPa	< 30

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website <https://www.solano-industries.com/en/>

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.