

MOLYDUVAL

Patricia CDA 68



Synthetic Compressor Fluid

This Synthetic Hydrocarbon oil is formulated from 100% synthetic base stocks for superior performance. Scheduled changes may be extended.

Properties

- * compatible with mineral oil
- * relative good seal compatibility, please ask for precise information in regard to your material
- * reduces oil consumption
- * reduces risk of burning and explosion

Applications

- * for vacuum pumps, mechanical and diffusions pumps
- * for rotary screw compressors
- * for Centrifugal Compressors

Technical Datas

Name		SHCLP68
Name		CLPSKW68
Base Fluid		PAO
Viscosity Class	ISO-VG	68
Pour point	°C	-54
Density 15°C	kg/m ³	840
Viscosity 40°C	mm ² /s	68
Viscosity 100°C	mm ² /s	10,3
Flash Point	°C	254
Ash Content	%	< 0,01
Viscosity Index		138
Lubricating Ability FZG Test, A/8.3/90	Grade	> 12
Demulsifying Ability		40/40/0
Foam Properties		5/10/5 0/0/0
Neutralisation Value	mg KOH/g	0,72
Air release 50°C, to 0,2% air	min	3
Sulfated ash	%	0,04

For further information, please see our website <https://www.solano-industries.com/en/>

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.