


Orgon OS



Silicone Free Separating Agent

Helps keep both mig & tig gun nozzles from clogging. Extends the life of welding tips. Helps provide cleaner & neater welds. Eliminates need for chipping, grinding or scraping off weld spatter. Prevents damage to the surrounding surface caused by flying weld spatter. Allows surfaces to be painted after welding. Allow easy removal of weld spatter from metal surfaces. Used by industrial plants, steel mills, ship yards, metal fabricating, robotic welding, maintenance companies & auto body shops.

Characteristics

- good lubrication performance
- biodegradable
- free of silicones
- good separating properties
- good moistening
- ecologically safe
- free of solvents
- inflammable
- enables painting or printer of tools
- high percentage of effective substances

Applications

- as release agent in MIG or MAG welding
- as release agent in welding
- as release agent for plastic and rubber molds, foams, and latex
- as release agent for welding robots
- as release agent in manufacturing with polyamides, PVC, polystyrols, rubber
- as release agent in electric welding

instructions

Apply a thin and even film with spraying systems. Can be diluted with water in a ratio of 1:1 up to 1:5. Spray to the area (10cm) near where the weld is to be made. Spatter can be easily removed.

Technical Datas

Color		white
Density 40°C	kg/m ³	980
Flash Point COC	°C	no

For further information, please see our website <https://www.solano-industries.com/en/>