


MOLYDUVAL

Supravit 14 CM



High Speed Grease

MOLYDUVAL Supravit 14 CM is a special high speed grease for lubrication of all kind of rolling and sliding bearings. Based on a special low viscosity carrier it is preferred for high speed bearings. It contains anti - corrosion additives which provide additional rust protection in case of water or damp penetrate into the lubrication point and a special wear reducing component.

Characteristics


- reduced friction
- very good low temperature characteristics
- long-life
- resistant against cold and hot water
- good corrosion protection

Applications

- for all kind of rolling and sliding bearings at high speeds, high pressures and even at often changing temperatures
- for lubrication of high speed gears with grease lubrication
- for instruments, apparatus and optical and electronic equipment (switchers, clocks, potentiometers aso.)
- for lubrication of worm gears and small engines

How To Use

With press or automatic lubrication system. Do not mix with other greases based on other oils or thickeners.



TECHNICAL DATAS	Specification	Unit	
Name	DIN 51502		KP2G-50
Base Fluid			Mineral Oil
Color			brown
Density, 15°C	SEB 181301	kg/m ³	900
Walked Penetration	DIN ISO 2137	·0,1mm	265-295
Classification NLGI	DIN 51818	NLGI	2
Dropping Point	DIN ISO 2176	°C	150
Operating Temperature Range		°C	-50 --> +105
Water resistance	DIN 51807	Grade	0-90
Rust preventing	DIN 51802	Grade	0/0
Oxidation resistance	DIN 51808	bar	< 0,3
Oil Separation	DIN 51817 N	%	< 3

For further information, please see our website <https://www.solano-industries.com/en/>

The technical information in this technical data sheet represents our present knowledge.

Because of complexity of tribological systems it does not form part of any sales contract as guaranteed properties of the delivered material.