


MOLYDUVAL

Circ A



High Temperature Metal-Compound

A special paste for the high-temperature lubrication of sliding surfaces and screw connections at particularly high pressures and the risk of burning. Seizing and rusting can be prevented even under difficult environmental conditions. A high proportion of specially selected solid lubricants - mainly metal powder - ensures a high separating effect with favorable thread friction values for hot screw connections. Proven for many years as an assembly and anti-seize paste in many applications.

Characteristics

- good anticorrosive properties
- exceptional lubricating and separating properties
- prevents seizure and rust
- free from mineral oil
- free of chlorine
- good sealing properties against corrosive gases and fluids
- free of lead and nickel
- resistant to water
- good heat deduction
- no resin forming
- low friction coefficient
- low residue forming

Applications

- for hot screw connections at turbines, exhausts, cogwheels, valves, chains, slidings, waves
- for slidings, guidelines, joints at slow moves and high pressures
- for bolts on brake systems, brake cams and back supports
- for bearings at calendars
- as release agent in high temperature range
- for pump seals in case of chlorine, gasoline, or other corrosive liquids
- for hot screws, nuts, locks, at extreme high temperatures
- for sliding surfaces in foundries, steel plants, galls production

Technical Datas

Color		silver
Base Fluid		Syn
Consistency Class NLGI		ca. 1-2
Viscosity Base Fluid, 40°C	mm ² /s	46
Density 15°C	kg/m ³	1200
Temperature Range dry lubrication, solid lubrication	°C	-40 -> +1200
Dropping Point	°C	no
Pour point Base Fluid	°C	-54

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.



For further information, please see our website <https://www.solano-industries.com>

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 31.07.2024