


MOLYDUVAL

Aladin FC Spray



PTFE Dry Lubricant

For the production of maintenance-free, colorless PTFE dry lubricating films with excellent release and sliding properties. These prevent wear, increase abrasion resistance, and prevent seizing. It features a very low coefficient of friction. Particularly effective at high sliding speeds; for high surface pressures, use Aladin MC.

Characteristics

- good anticorrosive properties
- reduces wear and friction
- very good tackiness
- low friction coefficient
- rejects dirt
- anthält Haftvermittler

Applications

- as release agent in metal casting, die casting, forging, pressing
- as sliding agent for wood
- as release agent for soft plastics
- for preservation of battery poles
- for coating plastics

Technical Datas

| | | |
|----------------------------|----|--------------|
| Color | | white |
| Basis | | PTFE |
| Temperature Range | °C | -180 -> +240 |
| Unit | ml | 400 |
| Pack Size spray can 400 ml | | + |
| Customs tariff number | | 320820 |

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.



For further information, please see our website www.solano-industries.com

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 15.09.2025