

MOLYDUVAL

Sekorex IL



Synthetic Biodegradable Inside Chain Oil

A synthetic ester based, very high treated lubrication oil for high temperature chains. Besides of its excellent high temperature stability it guarantees excellent wear protection and good corrosion protection. Qualified for chains and even suitable for bearings, slides and sliding surfaces at high temperatures. In case of very high temperatures it forms only less residues, and evaporates low.

Characteristics

- very high pressure ability
- compatible with mineral oil
- good low temperature characteristics
- low noise
- high flash point
- low viscosity
- good ageing resistance
- harmless
- low residue forming
- strong tackiness caused by very long molecules

Applications

- for chains in high temperature sectors
- for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- for chains in textile industry
- for chains in drying ovens, painting ovens, baking ovens, e.g. in the production of plasterboard and chipboard as well as glass or rock wool

Technical Datas

Color		yellow
Basis		ester
Viscosity 40°C	mm ² /s	5-20
Viscosity Index		140
Density 40°C	kg/m ³	860
Pack Size can 5 l		+
Pack Size drum 60 l		+
Pack Size drum 200 l		+
Pack Size Container 1000 l		+

For further information, please see our website <https://www.solano-industries.com>