


# MOLYDUVAL

## Tutela 11 Spray



### Longterm Corrosion Protection

A solvent containing, wax base, cutback corrosion preventive compound for outside storage or overseas transports of machine tools and parts. Forms a nearly dry film which is firm, white, translucent and non-tacky. It combines the basic requirements of good atomization, adhesion, and protection to insure that weld seams, joint and metal surfaces are protected. This pliable firm coating has a polar attraction to metal surfaces. The coating protects electrical connections and may prevent galvanic corrosion. It provides outstanding protection in corrosive environments.

### Properties

\* Below protection times, if indicated, are estimated times or such achieved in certain applications. These can deviate in other applications or under other conditions drastically. The indicated values should therefore only simplify you the selection from our product range. Real protection times must always be determined in practice.

- \* delivered liquid
- \* neutral to metal surfaces
- \* good tackiness
- \* even available in aerosol cans

### Applications

- \* for textile machinery
- \* for protection of tools and instruments in storage
- \* for protection of metal surfaces such as dies and moulds against corrosion during storage and transport
- \* for protection of steel tubes and profiles at outside storage
- \* for preservation of machines, gear boxes, turbines, vehicles, agricultural equipment
- \* for conservation and lubrication of wire ropes
- \* for the preservation and sealing of cavities.

### Technical Datas

Color		milky
Basis		Wax
Productiveness	m <sup>2</sup> /kg	7
Density 15°C	kg/m <sup>3</sup>	840
Protection Time Outdoor Storage	mon	12
Protection Time Indoor Storage	mon	24
Corrosion Protection Salt Spray Test	h	960
Corrosion Protection humidity chamber	h	2400
Film thickness	µm	50
Melting Point	°C	90
Drying Time	h	24

*Indicated protection times are approximate and may vary drastically in certain applications or under certain conditions, which is why they have to be confirmed in tests carried out by the user in each individual case.*



For further information, please see our website <https://www.solano-industries.com>

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.