


MOLYDUVAL

Ferroxin DS Spray



Wire Rope Spray

A solvent containing, wax base, cutback corrosion preventive compound for protection and lubrication wire ropes. It forms a dry wax like film which is firm, amber, translucent and non-tacky. It combines the basic requirements of good adhesion, protection and lubrication.

Characteristics

- free of graphite
- relative good resistant against alkaline fluids and gases
- delivered liquid
- forms flexible, closed wax film
- free of bituminous materials
- neutral to metal surfaces
- even available in hand spray bottles
- flexible even at low temperatures down to -30°C
- good tackiness
- very economic
- relative good compatibility with seals, plastics and paints, please check compatibility before application

Applications

- for protection of steel tubes and profiles at outside storage
- for preservation of machines, gear boxes, turbines, vehicles, agricultural equipment
- for conservation and lubrication of wire ropes
- for wire ropes at cranes, container appliances, open cast mining appliances and excavators

Technical Datas

Color		brown
Density 40°C	kg/m ³	860
Flash Point COC	°C	40
Drying Time 20°C, griffest	min	60
Productiveness	m ² /l	13
Corrosion Protection humidity chamber	h	500
Corrosion Protection Salt Spray Test	h	192
Pack Size spray can 400 ml		+



For further information, please see our website <https://www.solano-industries.com>